Intellegent softener valve for the ultimate in residential performance and reliability.







LED DISPLAY

## Fully adjustable ceramic valve for residential and light commercial use.

The RevV2.5 features innovative, patented ceramic discs for ultimate performance and reliability. The discs are abrasion and corrosion resistant, extending life while reducing maintenance costs. RevV2.5 valves have (4) four advanced programming options with fully adjustable cycles to minimize water usage.

They come equipped with signal output for external devices and interlock functions to connect to multiple valves in series. Available in LCD and LED versions, the valves offer remote handling from PLC or computer control.

### RevV2.5 Valve Features:

- Patented ceramic discs are corrosion and abrasion resistant for longer life and reduced maintenance.
- Multiple, programmable efficiency settings; grains exchanged per lb. of salt
- Bright, easy to read LCD and LED display options
- Long-term memory for program functions
- 72-hour memory backup
- No external PLC required to operate multiple control heads or external devices.



LCD DISPLAY



# **Operational Specifications**

Operational Pressure	Operational Water Temperature	Inlet Water Turbidity
20 - 88 psi	35°F - 125°F	<5NTU

### **Control Valve Parameters**

Inlet	Outlet	Drain	Brine	Base	Riser Tube	Hard Water Bypass
1"	1"	3/4"	3/8"	2.5" - 8NPSM	1.05" OD	Yes

Service @ 15 psi Drop	Peak Service @ 25 psi Drop
17.5 gpm	23 gpm



